

# FLAT ENCLOSURE HEATER

RC 016 | 01673.0-00



This small and flat enclosure heater offers optimum condensation protection in small enclosures, casings and installation spaces. The PTC heating element transfers its heat to an anodised aluminium profile. The compact contact heating is designed for continuous operation.

- Wide voltage range for electrical connection
- PTC heating element with dynamic response behavior
- Compact dimensions, use: e.g. as camera heater
- High heating capacity per volume



## OVERVIEW TECHNICAL DATA

Device type	Convection heaters
Protection class	II
Protection type	IP40
Heating element	PTC resistor (PTC)
Heater element	Aluminium profile, anodised
AC/DC	AC;DC
Operating voltage	120 V - 240 V
Inrush current	3 A
Frequency	50;60 Hz
Heating capacity	13 W
Surface temperature	< + 356 °F
Operating temperature	-49 °F - 158 °F
Operating humidity	≤90 % rF
Storage humidity	≤90 % rF
Storage temperature	-49 °F - 158 °F
Connection type	Connection cable
Connection	2x AWG 20, 300 mm
Mounting	Screw fixing
Installation position	any
Height	0.5 in
Width	1 in
Depth	1.4 in
Weight	1.4 oz
Note	Heating capacity measured at +20 °C (+68 °F) ambient temperature;When operating under AC/DC 140 V, the heating capacity is reduced by approx. 10 %.

TECHNICAL DRAWINGS

